

Aluminium alloy specification

Components	Impurities	Percentage (%)
Silicon		0.05 - 0.20
Zinc		3.50 - 5.00
Titanium		0.01 - 0.05
Bismuth		0.05 - 0.15
Indium		0.02 - 0.05
Aluminium	Remainder	
	Copper	0.01 max
	Iron	0.15 max
	Others each	0.02 max
	Others total	0.05 max



Electrochemical capacity: 2700 Ahr / Kg nominal

Solution potential: -1100 mV vs. Ag / AgCl reference cell nominal (in seawater)

Other specifications are available on request.

Note: All dimensions and weights are nominal. Dimensions in mm
 All data is subject to change without prior notice
 Anode is fitted with galvanised insert
 Anode can also be provided backside coated

Nett Weight: 4.0 Kg
 Gross Weight: 4.8 Kg

Date:			Cathodic Protection Division Rietdekkerstraat 16 P.O. Box 4222 2980 GE Roldenkerk Netherlands Tel: +31 (0)180 48 28 28 E-mail: sales@mme.nl www.mme-group.com		Projection: 	
	Order number:		Aluminium Alloy Hull Anode MME 4A		Scale: 1:7.5	
Rev. Description:	Drawn: PdG Checked: JdR Approved: PM	Date: 31-07-13 Date: 31-07-13 Date: 31-07-13	Project:	Dwg: MME 4A	Sheet 1/1	
Copyright MME. No part of this drawing may be copied, disclosed, or made public, in any form, without prior written consent of Material Meiringen Europe.						